


Performance 4S1P 11.05Ah 5C

MODEL NO: 0201-0401-10-02



APPLICATIONS

- Unmanned Aerial Systems (UAS) - Drones
- Unmanned Ground Vehicles (UGV)
- Mobile Energy Storage
- Robotics
- RC Vehicles

AVAILABLE UPGRADES

- Hard-case housing
- Integrated BMS
- Custom connector options
- Custom lead length configurations

TECHNICAL DATA

Chemistry	Li-Ion
Configuration	4S1P (4 cells total)
Nominal Voltage	13.6V
Maximum Voltage	16.6V
Minimum Voltage	12.0V (recommended cutoff)
Capacity	11.05Ah / 11,050mAh
Nominal Energy	150Wh
Max Continuous Discharge	55A (5C)
Max Charge Current	12A (1.09C)
Weight	15.8 oz (447 g)
Energy Density	336 Wh/kg
Dimensions	144 × 52 × 25 mm
Cycle Life	Varies per application, usage, and care
BMS	None
Power Lead	Customer-specified (XT90H-F / XT60H-F / AS150U)
Balance Lead	JST XHP-5



NDAA
COMPLIANT



ASSEMBLED
IN USA



NON-FEOC
CELLS

Safety Notes: This pack contains no integrated protection circuitry and is intended for controlled applications where charge/discharge management is externally regulated. Use only with compatible chargers and systems capable of monitoring cell voltages individually.

Disclaimer: Re:Build Battery Solutions is not liable for damages arising from use or misuse of this information. Specifications are for descriptive purposes only and subject to change without notice. Testing and validation under actual operating conditions are the responsibility of the end user.